

Din Rail Enclosures - DR Series

Designed to house and protect home automation control modules, MCB, RCD... and any DIN 43880 compatible device.

Available in a range of sizes to ensure the ideal fit for your project, the DR series boasts sturdy construction coupled with a premium finish.



Features:

- Compliant to AS/NZS 60670.1
- rated current : 100 Amp
- Protection: IP 20 for indoor Installation
- 1.2 mm Steel construction
- RAL 7035 grey colour powder coat
- Removable/ Reversible hinged door
- Lockable Door
- Knock outs top and bottom
- Include din rail and front plate
- 100 Amp earth and neutral bar, double screw, 5mm tunnel with M8 Screw for main cable
- Available in Surface And Flush mount



SURFACE MOUNT

Part Number	No of Rows	No of Poles	Height (mm)	Width (mm)	Depth (mm)	No of earth links (100Amp)	No of neutral links (100Amp)
DR116	1	16	308	455	115	1X16	1X16
DR216	2	32	458	455	115	1X22	1X22
DR316	3	48	608	455	115	2X16	2X16
DR416	4	64	758	455	115	3X16	3X16
DR516	5	80	908	455	115	4X16	4X16
DR616	6	96	1058	455	115	3X22	3X22
DR424	4	96	758	600	115	3X18	3X18
DR524	5	120	908	600	115	4X18	4X18
DR624	6	144	1058	600	115	5X18	5X18

FLUSH MOUNT

Part Number	No of Rows	No of Poles	Main Body			Door Panel		No of earth links (100Amp)	No of neutral links (100Amp)
			Height (mm)	Width (mm)	Depth (mm)	Height (mm)	Width (mm)		
DR216F	2	32	450	450	115	480	480	1X22	1X22
DR316F	3	48	600	450	115	630	480	2X16	2X16
DR416F	2	64	750	450	115	780	480	3X16	3X16