



Specification:

Din Rail Enclosure: 2 x 12 Poles (24 Modules)
(Includes Din Rail Insert and Escutcheon Front Plate)
Dimension: 400H x 300W x 150D - Single Door (1 Lock)
Degree of Protection: IP66
No. of Hinges: 2 (Reversible Hinged Door - 120 Degree Opening)
Door Seal: Polyurethane sealing
Terminal Bar: 100Amp Earth and Neutral Brass bar - 2 Screws, 5mm Tunnel, M8 Screw for main cabling
No. of Terminal Bar: 1 x 22-way Earth and 1 x 22-way Neutral Bar
Mounting Holes: 4x Ø 8.5mm Rear mounting holes
Mounting Bracket: 4x Galvanized steel wall mounting brackets with sealing gasket
Gland: Gland plate with sealing gasket
Earth studs: On door and body
Standard: Complies with IEC/EN 62208

Material:
Body & Door - Galvanised Sheet 1.2mm Thick
Gland Plate -Galvanised Sheet 1.2mm Thick
Finish: RAL 7035 Grey Colour Powder Coated

Company Confidential
This drawing and any information or descriptive material set out on it are the confidential and copyright property of Elecron Baal.® and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of *Elecron Baal.*

2 / 6 Cary Grove Minto NSW 2566, Australia
Tel. No: +61 2 72301357
email: info@elecronbaal.com.au
Website : <https://elecronbaal.com.au>

Projection: Third Angle

All Dimensions are in mm

Drawn:	KS	Description: 400 x 300 x 150 IPDR Enclosure			
Date:	26/04/2025	Dwg No: IPDR212			
Checked:	BA	Material:	Galvanized Steel	Weight:	8.2 kg
Issued on:	28/04/2025	Revision:	A	Scale:	NTS
		A3	Sheet:	1 / 1	