OS Steel Enclosures-Grey

General purpose **wall mount**

The Elekron Baal OS Range is constructed from Powder-Coated Galvanized steel. Designed for indoor and outdoor applications, however they are not recommended for coastal areas. Available in a wide range of sizes, and they are suitable for general industrial applications..





Features:

- IP 66 protection
- Material:
  - 1.2 mm thick Galvanized steel (Z80) up to 600Hx600W/700Hx500W Enclosures.
  - 1.5 mm thick Galvanized steel (Z80) for sizes 800Hx600W and above.
- Grey RAL 7035 Polyester powder coat (80-120 Micron, Textured finish).
- Concealed steel hinges
- Reversible door with 120 degree opening
- Two Bit Steel lock. Enclosures 500mm high and above have 2 Locks.
- Device Mounting plate:
  - 1.5mm galvanized Mounting plate up to 700Hx500W Enclosures.
  - 2mm galvanized Mounting plate with folded edges for sizes 800Hx600W and Above.
- Polyurethane door seal.
- 4x Ø8.5mm rear mounting holes.
- 4x Galvanized steel wall mounting brackets with sealing gasket.
- Gland plate with sealing gasket.
- Earth studs on door and body.
- Compliant with IEC/EN 62208 standard.

Part Number	Height (mm)	Width (mm)	Depth (mm)	No of Locks	Usable Depth (mm)
OS202015	200	200	150	1	138
OS302015	300	200	150	1	138
OS303015	300	300	150	1	138
OS303020	300	300	200	1	188
OS304020	300	400	200	1	188
OS403015	400	300	150	1	138
OS403020	400	300	200	1	188
OS404020	400	400	200	1	188
OS404025	400	400	250	1	238
OS404030	400	400	300	1	288

ELEKRON BAAL

Part Number	Height (mm)	Width (mm)	Depth (mm)	No of Locks	Usable Depth (mm)
OS406020	400	600	200	1	188
OS503020	500	300	200	2	188
OS504015	500	400	150	2	138
OS504020	500	400	200	2	188
OS505020	500	500	200	2	188
OS505025	500	500	250	2	238
OS604020	600	400	200	2	188
OS604025	600	400	250	2	238
OS604030	600	400	300	2	288
OS605025	600	500	250	2	238
OS606020	600	600	200	2	188
OS606025	600	600	250	2	238
OS606030	600	600	300	2	288
OS606040	600	600	400	2	388
OS705020	700	500	200	2	188
OS806020	800	600	200	2	188
OS806025	800	600	250	2	238
OS806030	800	600	300	2	288
OS806040	800	600	400	2	388
OS808025	800	800	250	2	238
OS808030	800	800	300	2	288
OS808050	800	800	500	2	488
OS1006020	1000	600	200	2	188
OS1008025	1000	800	250	2	238
OS1008035	1000	800	350	2	338
OS1206025	1200	600	250	2	238
OS1208020	1200	800	200	2	188
OS1208030	1200	800	300	2	288
OS1208040	1200	800	400	2	388