OS Steel Enclosures-Orange

General purpose **wall mount**



The Elekron Baal OS Range is constructed from Powder-Coated Galvanized steel. Designed for indoor and outdoor applications, however they are not recommended for coastal areas. Available in a wide range of sizes, and they are suitable for general industrial applications..



Features:

- IP 66 protection
- Material:
  - 1.2 mm thick Galvanized steel (Z80) up to 600Hx600W/700Hx500W Enclosures.
  - 1.5 mm thick Galvanized steel (Z80) for sizes 800Hx600W and above.
- Orange RAL 2008 Polyester powder coat (80-120 Micron, Textured finish).
- Concealed steel hinges
- Reversible door with 120 degree opening
- Two Bit Steel lock. Enclosures 500mm high and above have 2 Locks.
- Device Mounting plate:
  - 1.5mm galvanized Mounting plate up to 700Hx500W Enclosures.
  - 2mm galvanized Mounting plate with folded edges for sizes 800Hx600W and Above.
- Polyurethane door seal.
- 4x Ø8.5mm rear mounting holes.
- 4x Galvanized steel wall mounting brackets with sealing gasket.
- Gland plate with sealing gasket.
- Earth studs on door and body.
- Compliant with IEC/EN 62208 standard.

Part Number	Height (mm)	Width (mm)	Depth (mm)	No of Locks	Usable Depth (mm)
OS404020-O	400	400	200	1	188
OS604025-O	600	400	250	2	238
OS606025-O	600	600	250	2	238
OS806025-O	800	600	250	2	238
OS1008025-O	1000	800	250	2	238
OS1006020-O	1000	600	200	2	188
OS1208025-O	1200	800	250	2	238