


Black Cable Ties



Material :	Polyamide 6.6
Flammability Of Raw Material :	UL 94 - V2
Humidity Absorption :	2,7%-2,8% (23°C -50% R.H.)
Installation Temperature :	-10°C ~+85°C
Working Temperature :	-40°C ~+85°C
Max Sustaiaable Tempeature For Short Time:	+110°C

Good resistance to bases, oils, greases, oil derivates, chloride solvents. Limited resistance to acids.
 Not resistant to phenols.
 Carbon black addition gives a better UV resistance.



Black Cable Ties - UV Resistant								
PART NUMBER	WIDTH MM	LENGTH MM	MAX. BUNDLE DIA.		MIN. BUNDLE DIA.		MIN.TENSILE STRENGTH	
			MM	INCH	MM	INCH	N	IBS
TST-100M	2.5	100	22	0.87	2.0	0.079	80	18
TST-150I	3.6	150	35	1.65	3.0	0.118	180	42
TST-250I	3.6	250	65	2.76	3.0	0.118	180	42
TST-350I	3.6	350	100	3.94	3.0	0.118	180	42
TST-250ST	4.8	250	65	2.56	3.5	0.138	222	50
TST-350ST	4.8	350	90	3.54	3.5	0.138	222	50
TST-450ST	4.8	450	130	5.12	3.5	0.138	222	50
TST-550ST	4.8	550	160	6.30	3.5	0.138	222	50
TST-300HD	7.6	300	80	3.15	8.0	0.315	560	130
TST-450HD	7.6	450	130	5.12	8.0	0.315	560	130
TST-610HD	7.6	610	180	7.09	8.0	0.315	560	130
TST-400EHD	9	400	105	4.13	8.5	0.33	778	175
TST-550EHD	9	550	160	6.30	8.5	0.33	778	175
TST-710EHD	9	710	195	7.68	8.5	0.33	778	175
TST-530HSD	12.4	530	156	6.14	9.00	0.35	1140	250
TST-800HSD	12.4	800	230	9.06	9.00	0.35	1140	250

316 Stainless Steel Cable Ties



Technical Information

- ▷ Material: Stainless Steel Grade 316
- ▷ Working Temp: 80-°C to 538°C
- ▷ Description: Entirely metallic
- ▷ Flamability: Fireproof
- ▷ Other Properties: UV Resistant

Product Feature

- ▷ Ball-Lock type self-lock system.

316 Stainless Steel Cable Ties								
PART NUMBER	WIDTH	LENGTH	MAX. BUNDLE DIA.		MIN. BUNDLE DIA.		MIN.TENSILE STRENGTH	
			MM	INCH	MM	INCH	N	IBS
MGS-4.6*250	4.6	250	63	2.50	12.7	0.50	1000	225
MGS-4.6*400	4.6	400	102	4.00	12.7	0.50	1000	225
MGS-4.6*550	4.6	550	141	5.56	12.7	0.50	1000	225
MGS-7.9*250	7.9	250	63	2.50	12.7	0.50	2220	500
MGS-7.9*400	7.9	400	102	4.00	12.7	0.50	2220	500
MGS-7.9*550	7.9	550	141	5.56	12.7	0.50	2220	500
MGS-7.9*650	7.9	650	167	6.58	12.7	0.50	2220	500
MGS-12*400	12	400	102	4.02	25.4	1.00	3115	700
MGS-12*600	12	600	154	6.06	25.4	1.00	3115	700
MGS-12*750	12	750	188	7.40	25.4	1.00	3115	700